

MG CONNECT

Product Overview



YOUR FLEET'S SMART CO-PILOT

Key Benefits of MG Connect

- ✓ Predictive AI Analytics.
- ✓ Round-the-Clock Monitoring
- ✓ Instant Safety Alerts
- ✓ Customizable Modules
- ✓ Cost-Efficiency
- ✓ Advanced Security Measures
- ✓ Optimized Performance

AI Analysis & Monitoring

MG Connect seamlessly integrates with your vehicles' CAN bus system, collecting and analyzing critical data in real-time. Our advanced AI analyzes driver behavior (speed, acceleration, braking) and vehicle health, providing actionable insights to improve safety and efficiency.

Anticipation and Prevention of Accidents

MG Connect identifies risky driving behaviors like speeding, harsh braking, and erratic maneuvering. The system triggers immediate alerts for the fleet manager, allowing for real-time intervention. Driver behavior Data is also recorded for historical analysis and performance coaching allowing you to make data-driven decisions that improve your fleet's efficiency, safety, and profitability..



CONTACT US:



www.mobilegroup.com



Info@mobilegroup.co.il

CONNECT

© ALL RIGHTS RESERVED - Mobile Group Copyright 2024

Specifications provided by the manufacturer are subject to modification at any time without prior notification. Mobile Group disclaims any responsibility for inaccuracies or omissions in the provided information.



MOBILE
GROUP

MG CONNECT

Product Overview

SPECIFICATIONS:

• brand	Mobile Group
• model	Micro sim card
• sim	Card mg-connect
• cellular bands	GSM: B5(850)/B8(900)/B3(1800)/B2(1900) WCDMA: B1(2100)/B2(1900)/B4 (1700/2100 AWS1)/B5(850)/B8(900) LTE(FDD): B1(2100)/B2(1900)/B3(1800)/B4(1700)/B5(850)/B7(2600)/B8(900)/B12(700)/B20(800)/B28a(700)+b(700) LTE(TDD): B34(2100)/B38(2600)/B39(1900)/B40(2300)/B41(2500) TD-SCDMA: B34/B39
• work tempature	-20 c -75 c
• storage tempature	-30 c -80 c
• work voltage	Dc 9v - 36v (60v Protection)
• work current	12v or 24v\ average 35mA
• sleep current	12v or 24v > 10mA Average
• battery	140 mAh (4.3v Polymer batery)
• work humidity	10% - 85% RH non-condensing
• position	BDS + GPS + GSM
• rely	One extra relay (Pull down)
• acc detection input	ACC detection port one way
• can detection	1 x CAN
• 1 wire	1 x
• rs232	TX/ RX/ GND
• shell material	ABS plastic

CONTACT US:



www.mobilegroup.com



Info@mobilegroup.co.il

© ALL RIGHTS RESERVED - Mobile Group Copyright 2024

Specifications provided by the manufacturer are subject to modification at any time without prior notification. Mobile Group disclaims any responsibility for inaccuracies or omissions in the provided information.



MOBILE
GROUP

MG CONNECT

Product Overview

SPECIFICATIONS:

• sleep current	12v or 24v > 10mA Average
• battery	140 mAh (4.3v Polymer battery)
• work humidity	10% - 85% RH non-condensing
• position	BDS + GPS + GSM
• relay	One extra relay (Pull down)
• acc detection input	ACC detection port one way
• can detection	1 x CAN
• 1 wire	1 x
• rs232	TX/ RX/ GND
• shell material	ABS plastic



CONTACT US:

 www.mobilegroup.com

 Info@mobilegroup.co.il

CONNECT

© ALL RIGHTS RESERVED - Mobile Group Copyright 2024

Specifications provided by the manufacturer are subject to modification at any time without prior notification. Mobile Group disclaims any responsibility for inaccuracies or omissions in the provided information.